



LED BULB



ITEM NO.:

MA6010W865K

MA6010W840K

MA6010W830K



Product size



Key Features

- Energy saving, lightweight design.
- Energy saving, lightweight design with 10W consumption capable of replacing 60W incandescent bulbs.
- Eco-Friendly: No infrared or ultraviolet, low temperature, mercury free.
- Soft light source does not flicker, more suitable for lighting applications.
- E27 lamp holder, home lamp holder can be installed directly.
- Comply with Taiwan CNS standard certification specifications.
- Non-directional, luminous Angle 210 degrees.
- This product is covered by product liability insurance.

Precautions

1. Do not install the bulb on a faulty circuit to avoid fire hazards.
2. Ensure the correct voltage and lamp holder before installation.
3. This bulb is not suitable for lamps with dimmers.
4. Suitable for Indoor only, avoid wet or poorly ventilated environments.
The environment and closed ventilation of poor lighting.
5. Do not touch the bulb directly when lit.
6. Be sure to turn off the power before replacing the bulb.
7. If the LED bulb is significantly heavier than the replaced light source, Ensure the lamp holder can support the added weight to avoid the mechanical instability and potential damage.



Product parameter

Voltage	100-240VAC	Wires of driver/holder	E27
Power-factor	≥ 0.9	Color rendering index(Ra)	RA ≥ 80
Power Efficiency	90%	Beam Angle	210°
LED Quantity	16D	Juction Temperature	40°C
Circuit	2B8C	Operation Temperature	0°C~40°C
Input Watts	10W	Storage Temperature	-20°C~40°C
Light Output Ratio(LOR)	120lm/W	Ip Rating	IP20
LED Initial flux	1200lm	Material	PBT+Aluminum
Surge level	2.5kV	Surface color	White
Voltage withstand level	1.5kV/5mA	Unit Weight	46g
Working Life Span	2 years	Color Temperature	6500K/4000K/3000K