



Product Service

CERTIFICATE

No. B 055365 0010 Rev. 00

Holder of Certificate: Mean Well Enterprise Co., Ltd.

No.28, Wuquan 3rd Rd.
Wugu Dist.
248 New Taipei City
TAIWAN

Certification Mark:



Product:

**Component fan
(DC FAN)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 6821024017201A

Valid until: 2029-04-17

Date, 2024-05-16

(Bruce Zhang)

CERTIFICATE

No. B 055365 0010 Rev. 00

Model(s):

CH(a)4012(b)L-(c)20(d), CH(a)4012(b)M-(c)20(d),
CH(a)4012(b)H-(c)20(d), CH(a)4012(b)X-(c)20(d),
CH(a)4012(b)Y-(c)20(d), CH(a)4024(b)L-(c)20(d),
CH(a)4024(b)M-(c)20(d), CH(a)4024(b)H-(c)20(d),
CH(a)4024(b)X-(c)20(d), CH(a)4024(b)Y-(c)20(d),
CH(a)4024(b)U-(c)20(d), CH(a)6024(b)L-(c)25(d),
CH(a)6024(b)M-(c)25(d), CH(a)6024(b)H-(c)25(d),
CH(a)6024(b)X-(c)25(d), CH(a)6024(b)Y-(c)25(d),
CH(a)6012(b)L-(c)10(d), CH(a)6012(b)M-(c)10(d),
CH(a)6012(b)H-(c)10(d), CH(a)6012(b)X-(c)10(d),
CH(a)6012(b)Y-(c)10(d), CH(a)6012(b)U-(c)10(d)

[(a)= 'A' or 'T', indicates type of lead wire, 'A' indicates lead wires '+' and '-', 'T' indicates lead wires '+', '-' and 'FG' wire which used for detecting running status of fan;

(b)= 'S', 'R', 'B', 'C' indicates type of bearing, 'S' indicates sleeve bearing, 'R' indicates hydraulic bearing, 'B' indicates multiple ball bearing, 'C' indicates single ball bearing;

(c)= 'A', 'R', 'S', 'W' or blank indicates the functionality of product, 'A' or blank indicates none rotate detection and FG and thermo-control speed or pulse width modulation; 'R' indicates rotate detection automatic restart and locked current protection; 'S' indicates thermo-control speed, automatic restart and locked current protection; 'W' indicates pulse width modulation and automatic restart and locked current protection;

(d)= 'A'-'Z' indicates code of supplier, which is not affect safety compliance.

'L', 'M', 'H', 'X', 'Y' and 'U' indicates speed degree, 'L' indicates low speed, 'M' indicates medium speed, 'H' indicates high speed, 'X' indicates very high speed, 'Y' indicates most high speed, 'U' indicates extremely high speed.]

Brand Name:

MEAN WELL



CERTIFICATE

No. B 055365 0010 Rev. 00

Parameters:

Ratings: See below table for details

Protection Class: III

Degree of Protection: IPX0

Remarks:

- The maximum operating temperature is 70°C.
- Built-in component, suitable enclosure and type of supply connection should be provided by end system.
- When installing the component, all requirements of the relevant standard must be fulfilled.

Tested according to: EN IEC 62368-1:2020/A11:2020

CERTIFICATE

No. B 055365 0010 Rev. 00

Model No.	Rated Voltage (VDC)	Rated Current (A)
CH(a)4012(b)L-(c)20(d)	12	0.10
CH(a)4012(b)M-(c)20(d)	12	0.15
CH(a)4012(b)H-(c)20(d)	12	0.18
CH(a)4012(b)X-(c)20(d)	12	0.50
CH(a)4012(b)Y-(c)20(d)	12	0.55
CH(a)4024(b)L-(c)20(d)	24	0.05
CH(a)4024(b)M-(c)20(d)	24	0.10
CH(a)4024(b)H-(c)20(d)	24	0.15
CH(a)4024(b)X-(c)20(d)	24	0.20
CH(a)4024(b)Y-(c)20(d)	24	0.30
CH(a)4024(b)U-(c)20(d)	24	0.50
CH(a)6024(b)L-(c)25(d)	24	0.08
CH(a)6024(b)M-(c)25(d)	24	0.15
CH(a)6024(b)H-(c)25(d)	24	0.25
CH(a)6024(b)X-(c)25(d)	24	0.35
CH(a)6024(b)Y-(c)25(d)	24	0.50
CH(a)6012(b)L-(c)10(d)	12	0.10
CH(a)6012(b)M-(c)10(d)	12	0.20
CH(a)6012(b)H-(c)10(d)	12	0.30
CH(a)6012(b)X-(c)10(d)	12	0.40
CH(a)6012(b)Y-(c)10(d)	12	0.50
CH(a)6012(b)U-(c)10(d)	12	0.60